

Telehandler / Zoom Boom

Used Telehandler Ohio - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial equipment is commonly used in a variety of industries including agriculture. Similar to a crane and a forklift as it has a boom allowing it to extend forwards and upwards. Many different attachments can be used at the end of the articulating boom to facilitate a wide number of jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The main telehandler attachment is the pallet forks. These attachments help the operator transport different sized loads to many locations that would be considered unreachable with a traditional forklift. Telehandlers allow cargo pallets to be loaded and unloaded from a trailer and placed on high locations such as racking or rooftops. Normally, high rooftop applications would require the use of a crane; however, telehandlers can complete this task more efficiently. It can be expensive and impractical to rely on a crane or expansive industrial equipment to finish particular tasks. A bucket or bucket grab is the most popular telehandler attachment in the agricultural industry. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler units often work together with a crane jib. Numerous attachments can be utilized including power booms, grain buckets, dirt buckets and rotators. Agricultural models can be outfitted with power take-off and 3-point linkage, making the telehandler and exceptionally useful. Interestingly enough, the machines' main advantage is also its' biggest limitation. The boom acts as a lever when it extends or raises with heavy loads. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. There are sensors and computers available on newer models. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. The lifting capacity is enhanced by front stabilizers that maximize the lifting capacity from a stationary position. A stabilizing rotary joint between the upper and lower frames may be called a mobile crane that can use a bucket. There are compact telehandler models that differ in boom design, size, reach and weight. Telehandlers that weigh 11,000 pounds or less fall into the compact category. Compact models feature a two- stage boom design in comparison to the three or four boom design that is common with larger units. A low pivot boom ensures better operator visibility for transporting loads on compact units. Obviously, the compact telehandler has narrower and tinier dimensions. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. These versatile machines make the compact telehandler extremely popular. It may be used as a tool carrier or a pick and place machine. This machine is often used in locations that are cramped and tight. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. Telehandlers can enter internal building access in hard-to-reach locations. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Agri-business and farming applications rely on telehandlers for a variety of

jobs. Telehandlers come with crab steering or two or four-wheel drive options. This machine can traverse longer distances with two-wheel drive at higher speeds to facilitate easy travel between worksites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering enhances the units' maneuverability while allowing each set of wheels to move forty-five degrees to the right or left. Compact telehandlers have varying cab environments. On the lower-end models, a rollover protective cage structure is in place for safety. Newer units come with windshield wipers, a defroster, a heater and a totally enclosed cab. Compact units feature spacious cab accommodations to keep operators totally comfortable. Extra amenities including air conditioning, satellite radio, suspension seats, tilt steering and cup holders are available. Different high-flow auxiliary hydraulics and high-pressure hydraulics run the variety of attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Ground engaging work is often completed by compact units. Adding a bucket attachment can make a compact telehandler transform into a mini excavator. Light-duty to heavy-duty buckets can be attached for transferring material, side-shifting and rotating fork carriages are relied on for pick and place situations, augers for drilling post holes or planting trees or pier supports, truss booms for extending reach, crane hooks, brooms for sweeping and more. Skid steer attachments are being made for versatility and other compact telehandler designs.